

Media: air
 Pressure range: 0 to 9 Bar max
 Media temp: -10°C +60°C max
 Ambient temperature: -10° to +60°C
 Mounting: any position

5/2 Hand Control

1/8 1/4

Mechanical Valves

5 WAY DIRECT ACTING

0 – 9 Bar

TYPE MSV8652



PRESSURE

| Ø Port | Ø Orifice (mm²) | Pressure Rating (Bar) | | | Operator | | | Part Number |
|----------|-----------------|-----------------------|--------|-----|----------------------|-----------------|---------|--------------------------|
| | | Min ΔP | Max ΔP | Max | Type | Standard Colour | Picture | |
| 1/8 (01) | 1/8" 14mm² | 0 | 9 | 10 | Roller | - | | MSV8652 + port (01/02)R |
| | | 0 | 9 | 10 | Twist Selector | Black | | MSV8652+ port (01/02)TB |
| | | 0 | 9 | 10 | Long Twist selector | Black | | MSV8652+ port (01/02)LB |
| | | 0 | 9 | 10 | Palm Button Mushroom | Red | | MSV8652+ port (01/02)PB |
| 1/4 (02) | 1/4 18mm² | 0 | 9 | 10 | Palm Button Flush | Red | | MSV8652+ port (01/02)PP |
| | | 0 | 9 | 10 | Palm Button Extended | Red | | MSV8652+ port (01/02)PPL |
| | | 0 | 9 | 10 | Detent Button | Red | | MSV8652+ port (01/02)EB |
| | | 0 | 9 | 10 | Push Pull Button | Black | | MSV8652+ port (01/02)PH |

OPTIONS

NPT Thread (MSV8652-01/2N)
 Optional button colours Green (G), Black (B) or Yellow(Y) (PB, PP, PPL)
 Panel diameter 25mm

CONSTRUCTION

Body : Aluminium alloy, Panel dimension 30mm, internal parts : Stainless steel, Seals and gaskets : NBR

OVERALL DIMENSIONS

