



No	Part Name	Material
1	Gauge	-----
2	Cover	316 Stainless Steel
3	U-Ring	VITON
4	Shaft	316 Stainless Steel
5	Sealing Spacer	VITON
6	Shaft	316 Stainless Steel
7	Main Body	316 Stainless Steel
8	Diaphragm Cover	316 Stainless Steel
9	Diaphragm	EPDM
10	Fixed Bolt	304 Stainless Steel
11	Spring	Spring Steel
12	Spring Cover	316 Stainless Steel
13	Spring Washer	Bronze
14	Adjusting Bolt	304 Stainless Steel

Item No	BSPT	H	L	D	CV*
RFLT-15-S	1/2"	110	70	105	2.4
RFLT-20-S	3/4"	125	85	105	9
RFLT-25-S	1"	125	90	105	11
RFLT-40-S	1 1/2"	155	115	145	21
RFLT-50-S	2"	155	120	145	25

Unit : mm

\* Applied Fluid : Water, Air.

\* Pressure Adjusting Range : 0.2kgf/cm<sup>2</sup> ~ 1.5kgf/cm<sup>2</sup>  
 (\* Special order is needed for particular fluid.)

\* Applied Temperature : -15°C ~ 100°C

\* Pressure gauge indicates the Inlet pressure.