



Media: air – gas - vacuum
 Pressure range: 0 to 8 Bar max
 External Pilot: 1.5 to 8 Bar
 Media temperature: +80°C max
 Ambient temperature: -10°C to +80°C max
 Mounting: any position
 Weight: 135, 145, 220g



5/2 & 5/3 Pneumatic Valve

1/4" 22mm Width
 5/2 S/RETURN or 5/2 & 5/3 D/ACTING
 DIRECT ACTING
 0 – 8 Bar
 TYPE SB520



5/2 Way Spring Return SB520S Series

Ø Port BSP	Ø Orifice (mm ²)	Pressure Rating (Bar) ΔP		Max Work	Part Number	Width	
		Min	Max				
1/4	18	0	8	10	SB52002S	22mm	

5/2 Way Double Acting SB520D Series

Ø Port BSP	Ø Orifice (mm ²)	Pressure Rating (Bar) ΔP		Max Work	Part Number	Width	
		Min	Max				
1/4	18	0	8	10	SB52002D	22mm	

5/3 Way Double Acting SB530D Series

Ø Port BSP	Ø Orifice (mm ²)	Pressure Rating (Bar) ΔP		Max Work	Part Number	Width	
		Min	Max				
1/4	14	0	7	10	SB53002D	22mm	

OPTIONS

NPT Thread
 BF Manifold c/w Gaskets and Fixing Kit (cost is per station Ref: BF X Number of stations)
 BM530X Exhaust centre or BM530Y Pressure centre

CONSTRUCTION

Body: Anodised Aluminium
 Tube and internal parts: Stainless steel
 Seals and gaskets: NBR

OVERALL DIMENSIONS

SB520S

SB520D

SB530D

